

### Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878 Issue date: 17-2-2014 Revision date: 19-9-2022 Supersedes: 19-7-2021 Version: 4.4

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### **1.1. Product identifier**

Product form	: Mixture
Product name	: Eurol Screenwash Concentrate
UFI	: 060J-660J-2702-AF3N
Product code	: E502260
Type of product	: Cleaner,Detergent
Product group	: Trade product

#### **1.2. Relevant identified uses of the substance or mixture and uses advised against**

#### 1.2.1. Relevant identified uses

Intended for general public Main use category Use of the substance/mixture

: Industrial use,professional use,Consumer use: Screenwash anti-freeze.

#### 1.2.2. Uses advised against

No additional information available

#### 1.3. Details of the supplier of the safety data sheet

Eurol bv. B.V. Energiestraat 12 P.O. Box P.O. Box 135 NL– 7442 DA Nijverdal The Netherlands T +31 548 615165 reach@eurol.com - www.eurol.com

#### 1.4. Emergency telephone number

Emergency number

: +31 79 3467 808 EVOFENEDEX

Country	Organisation/Company	Address	Emergency number	Comment
Ireland	National Poisons Information Centre Beaumont Hospital	PO Box 1297 Beaumont Road 9 Dublin	+353 1 809 2566 (Healthcare professionals- 24/7) +353 1 809 2166 (public, 8am - 10pm, 7/7)	
Malta	Medicines & Poisons Info Office	Mater Dei Hospital MSD 2090 Msida	+356 2545 6508	
United Kingdom	National Poisons Information Service (Birmingham Centre) City Hospital	Dudley Road B18 7QH Birmingham	0344 892 0111	Only for healthcare professionals
United Kingdom	NHS 111/NHS 24/NHS Direct	Edinburgh	111 0845 4647	or call a doctor

SECTION 2: Hazards identification		
2.1. Classification of the substance or mixture		
Classification according to Regulation (EC) No. 1272/2008 [CLP]		
Flammable liquids, Category 3	H226	
Serious eye damage/eye irritation, Category 2	H319	

### Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

#### Full text of H- and EUH-statements: see section 16

#### Adverse physicochemical, human health and environmental effects

#### No additional information available

2.2. Label elements		
Labelling according to Regulation (EC) No. 1272/2008 [CLP]		
Hazard pictograms (CLP)		
	GHS02 GHS07	
CLP Signal word Hazard statements (CLP)	: Warning : H226 - Flammable liquid and vapour. H319 - Causes serious eye irritation.	
Precautionary statements (CLP) Child-resistant fastening Tactile warning	<ul> <li>P102 - Keep out of reach of children.</li> <li>P210 - Keep away from heat, hot surfaces, open flames, sparks. No smoking.</li> <li>P280 - Wear eye protection, protective gloves.</li> <li>P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.</li> <li>P337+P313 - If eye irritation persists: Get medical advice/attention.</li> <li>P501 - Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.</li> <li>Not applicable</li> </ul>	
2.3. Other hazards		
Other hazards not contributing to the classification	: Material can accumulate some static charge during transfer. Flammable or explosive	

vapour/air mixtures may be formed.

Contains no PBT/vPvB substances ≥ 0.1% assessed in accordance with REACH Annex XIII

#### SECTION 3: Composition/information on ingredients

#### 3.1. Substances

### Not applicable

#### 3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
ethanol; ethyl alcohol substance with national workplace exposure limit(s) (GB, IE)	CAS-No.: 64-17-5 EC-No.: 200-578-6 EC Index-No.: 603-002-00-5 REACH-no: 01-2119457610- 43	≥ 50	Flam. Liq. 2, H225 Eye Irrit. 2, H319
ethane-1,2-diol substance with national workplace exposure limit(s) (GB, IE, MT); substance with a Community workplace exposure limit	CAS-No.: 107-21-1 EC-No.: 203-473-3 REACH-no: 01-2119456816- 28	5 – 10	Acute Tox. 4 (Oral), H302 STOT RE 2, H373
butanone; ethyl methyl ketone substance with national workplace exposure limit(s) (GB, IE, MT); substance with a Community workplace exposure limit	CAS-No.: 78-93-3 EC-No.: 201-159-0 EC Index-No.: 606-002-00-3 REACH-no: 011-2119457290- 43	0,1 – 1	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336

Full text of H- and EUH-statements: see section 16

### Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

SECTION 4: First aid measures	
4.1. Description of first aid measures	
First-aid measures general	: Seek medical attention if ill effect develops.
First-aid measures after inhalation	: When symptoms occur: go into open air and ventilate suspected area. Allow the victim to rest. If you feel unwell, seek medical advice.
First-aid measures after skin contact	: Remove affected clothing and wash all exposed skin area with mild soap and water, followed by warm water rinse. Seek medical attention if ill effect or irritation develops.
First-aid measures after eye contact	: Ensure adequate flushing of eyes by separating eyelids with the fingers. Remove contact lenses, if present and easy to do. Continue rinsing. Obtain medical attention if pain, blinking, tears or redness persist.
First-aid measures after ingestion	: Do not induce vomiting. If vomiting occurs spontaneously, keep head below the hips to prevent aspiration. Vomiting after ingestion may cause aspiration into the lungs, which may cause severe lungdamage or death.
4.2. Most important symptoms and effects,	both acute and delayed
Symptoms/effects after inhalation	: High concentration of vapours may induce: headache, dizziness, drowsiness, nausea and vomiting.
Symptoms/effects after skin contact	: Unlikely to cause harm to the skin on brief or occasional contact but prolonged or repeated exposure may lead to dermatitis.
Symptoms/effects after eye contact	: Unlikely to cause more than transient stinging or redness if accidental eye contact occurs. Contact with the eyes is likely to be irritating. Harmful: may cause lung damage if swallowed.
Symptoms/effects after ingestion	: Bad taste. Vomiting after ingestion may cause aspiration into the lungs, which may cause severe lungdamage or death.
Symptoms/effects upon intravenous administration	: No information available.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures		
5.1. Extinguishing media		
Suitable extinguishing media Unsuitable extinguishing media	<ul> <li>Alcohol-resistant foam. Dry powder. Water fog. Carbon dioxide.</li> <li>Do not use a heavy water stream. Use of heavy stream of water may spread fire.</li> </ul>	
5.2. Special hazards arising from the substance or mixture		
Fire hazard Explosion hazard Hazardous decomposition products in case of fire	<ul> <li>Combustion generates: CO, CO2.</li> <li>May form flammable/explosive vapour-air mixture.</li> <li>CO, CO2.</li> </ul>	
5.3. Advice for firefighters		
Precautionary measures fire Firefighting instructions Protection during firefighting Other information	<ul> <li>Do not enter fire area without proper protective equipment, including respiratory protection.</li> <li>Use water spray or fog for cooling exposed containers.</li> <li>Use self-contained breathing apparatus and chemically protective clothing.</li> <li>Prevent fire fighting water from entering the environment. Sweep up and remove to a suitable, clearly marked container for disposal in accordance with local regulations. Heavier than air, vapours may travel long distances along ground, ignite and flash back to source.</li> </ul>	

# SECTION 6: Accidental release measures 6.1. Personal precautions, protective equipment and emergency procedures

General measures

: Prevent soil and water pollution. Spill area may be slippery. Prevent build-up of electrostatic charges (e.g, by grounding). Remove all sources of ignition.

### Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

6.1.1. For non-emergency personnel	
Protective equipment	: When the risk of skin exposure is high (e.g. when cleaning up spillages or if there is a risk of splashing) then chemical resistant aprons and/or impervious chemical suits and boots will be required.
Emergency procedures	: Consider evacuation.
6.1.2. For emergency responders	
Protective equipment	: When the risk of skin exposure is high (e.g. when cleaning up spillages or if there is a risk of splashing) then chemical resistant aprons and/or impervious chemical suits and boots will be required.
Emergency procedures	: No specific measures are necessary.
6.2. Environmental precautions	

Prevent soil and water pollution. Dike for recovery or absorb with appropriate material. Notify authorities if product enters sewers or public waters. Prevent entry to sewers and public waters.

6.3. Methods and material for containment and cleaning up		
For containment	: Contain large spillage with sand or earth.	
Methods for cleaning up	<ul> <li>Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Take up large spills with pump or vacuum and finish with dry chemical absorbent.</li> </ul>	
Other information	: Use suitable disposal containers. Sweep up and remove to a suitable, clearly marked container for disposal in accordance with local regulations. On water, recover/skim from surface and pour out in disposal container.	

## 6.4. Reference to other sections

#### For further information refer to section 13.

SECTION 7: Handling and storage		
7.1. Precautions for safe handling		
Additional hazards when processed	In use, may form flammable vapour-air mixture. Empty containers retain product residue (solid, liquid, and/or vapor) and can be dangerous. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, static electricity, or other sources of ignition. They may explode and cause injury or death. Empty containers should be completely drained, properly closed, and promptly returned to a drum reconditioner or disposed of properly.	
Precautions for safe handling	: Do not eat, drink or smoke when using this product. Avoid prolonged and repeated contact with skin. May be dangerously slippery if spilled. Take off contaminated clothing. Where contact with eyes or skin is likely, wear suitable protection. Prevent build-up of electrostatic charges (e.g, by grounding). No naked lights. No smoking. Provide local exhaust or general room ventilation to minimize mist and/or vapour concentrations.	
Hygiene measures	: Take all necessary measures to avoid accidental discharge of products into drains and waterways due to the rupture of containers or transfer systems. Handle in accordance with good industrial hygiene and safety practice. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Where contact with eyes or skin is likely, wear suitable protection. Wash contaminated clothing before reuse. Cloth, paper and other materials that are used to absorb spills present a fire hazard.	
7.2. Conditions for safe storage, including any incompatibilities		
Technical measures	: Store in a dry place. Store in a closed container. Store away from direct sunlight or other heat sources. Prevent build-up of electrostatic charges (e.g, by grounding).	
Storage conditions	: Keep container tightly closed. Keep only in original container.	
Incompatible products	: Reacts vigorously with strong oxidizers and acids.	
Maximum storage period	: 5 year	
Storage temperature	: ≤ 40 °C	
Information on mixed storage	: Keep away from : Oxidizing materials. Strong acids. : Store at ambient temperature.	
Storage area Special rules on packaging	: Keep container tightly closed and dry.	
epecial aloo on paolaging		

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

### 7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection			
8.1. Control parameters			
8.1.1 National occupational exposure and biological	8.1.1 National occupational exposure and biological limit values		
ethanol; ethyl alcohol (64-17-5)			
Ireland - Occupational Exposure Limits			
Local name	Ethanol [Ethyl alcohol]		
OEL (15 min ref) (ppm)	1000 ppm		
Regulatory reference	Chemical Agents Code of Practice 2021		
United Kingdom - Occupational Exposure Limits			
Local name	Ethanol		
WEL TWA (mg/m³)	1920 mg/m³		
WEL TWA (ppm)	1000 ppm		
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE		
ethane-1,2-diol (107-21-1)			
EU - Indicative Occupational Exposure Limit (IOEL)			
Local name	Ethylene glycol		
IOELV TWA (mg/m³)	52 mg/m³		
IOELV STEL (mg/m³)	104 mg/m³		
IOELV STEL (ppm)	40 ppm		
Notes	Skin		
Regulatory reference	COMMISSION DIRECTIVE 2000/39/EC		
Ireland - Occupational Exposure Limits			
Local name	Ethane-1,2-diol [Ethylene glycol]		
OEL (8 hours ref) (mg/m³)	10 mg/m³ particulate 52 mg/m³ vapour		
OEL (8 hours ref) (ppm)	20 ppm vapour		
OEL (15 min ref) (mg/m3)	104 mg/m³ vapour		
OEL (15 min ref) (ppm)	40 ppm vapour		
Regulatory reference	Chemical Agents Code of Practice 2021		
Malta - Occupational Exposure Limits			
Local name	Ethylene glycol		
OEL TWA (mg/m³)	52 mg/m³		
OEL TWA (ppm)	20 ppm		
OEL STEL (mg/m <sup>3</sup> )	104 mg/m <sup>3</sup>		
OEL STEL (ppm)	40 ppm		
Remark	Skin # Ġilda		
Regulatory reference	S.L.424.24 - Chemical Agents at Work Regulations (L.N.57 of 2018)		

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

ethane-1,2-diol (107-21-1)		
United Kingdom - Occupational Exposure Limits		
Local name	Ethane-1,2-diol	
WEL TWA (mg/m³)	10 mg/m³ particulate 52 mg/m³ vapour	
WEL TWA (ppm)	20 ppm vapour	
WEL STEL (mg/m³)	104 mg/m³ vapour	
WEL STEL (OEL STEL) [ppm]	40 ppm vapour	
Remark (WEL)	Sk (Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity)	
butanone; ethyl methyl ketone (78-93-3)		
EU - Indicative Occupational Exposure Limit (IOEL)		
Local name	Butanone	
IOELV TWA (mg/m³)	600 mg/m <sup>3</sup>	
IOELV TWA (ppm)	200 ppm	
IOELV STEL (mg/m <sup>3</sup> )	900 mg/m³	
IOELV STEL (ppm)	300 ppm	
Regulatory reference	COMMISSION DIRECTIVE 2000/39/EC	
Ireland - Occupational Exposure Limits		
Local name	Methyl ethyl ketone (MEK)	
OEL (8 hours ref) (mg/m <sup>3</sup> )	600 mg/m <sup>3</sup>	
OEL (8 hours ref) (ppm)	200 ppm	
OEL (15 min ref) (mg/m3)	900 mg/m³	
OEL (15 min ref) (ppm)	300 ppm	
Regulatory reference	Chemical Agents Code of Practice 2021	
Malta - Occupational Exposure Limits		
Local name	Butanone	
OEL TWA (mg/m³)	600 mg/m³	
OEL TWA (ppm)	200 ppm	
OEL STEL (mg/m³)	900 mg/m³	
OEL STEL (ppm)	300 ppm	
Regulatory reference	S.L.424.24 - Chemical Agents at Work Regulations (L.N.57 of 2018)	
United Kingdom - Occupational Exposure Limits		
Local name	Butan-2-one (methyl ethyl ketone)	
WEL TWA (mg/m³)	600 mg/m³	
WEL TWA (ppm)	200 ppm	
WEL STEL (mg/m³)	899 mg/m³	
WEL STEL (OEL STEL) [ppm]	300 ppm	
Remark (WEL)	Sk (Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity)	
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE	

### Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

butanone; ethyl methyl ketone (78-93-3)		
United Kingdom - Biological limit values		
Local name	Butan-2-one (methyl ethyl ketone)	
BMGV 70 µmol/l Parameter: butan-2-one - Medium: urine - Sampling time: Post shift		
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE	

#### 8.1.2. Recommended monitoring procedures

No additional information available

#### 8.1.3. Air contaminants formed

No additional information available

#### 8.1.4. DNEL and PNEC

No additional information available

#### 8.1.5. Control banding

No additional information available

#### 8.2. Exposure controls

#### 8.2.1. Appropriate engineering controls

#### Appropriate engineering controls:

Provide for appropriate exhaust ventilation at places of vapours accumulation. Use explosion-proof equipment. Provided an air-filtering/air-purifying respirator is suitable, a filter for particulates can be used for mist or fume. Use filter type P or comparable standard. A combination filter for particles and organic gases and vapours (boiling point >65°C) may be required if vapour or abnormal odour is also present due to high product temperature. Use filter type AP or comparable standard. Respiratory protective equipment must be checked to ensure it fits correctly each time it is worn. Large quantities: Contain large spillage with sand or earth.

#### 8.2.2. Personal protection equipment

#### Personal protective equipment:

Gloves. In case of splash hazard: safety glasses. Respiratory protective equipment is not normally required where there is adequate natural or local exhaust ventilation to control exposure.

#### Personal protective equipment symbol(s):



#### 8.2.2.1. Eye and face protection

#### Eye protection:

Safety glasses with side shields. Eye protection should only be necessary where liquid could be splashed or sprayed

#### 8.2.2.2. Skin protection

#### Skin and body protection:

No special clothing/skin protection equipment is recommended under normal conditions of use. Avoid repeated or prolonged skin contact. If repeated skin contact or contamination of clothing is likely, protective clothing should be worn. Equipment should conform to EN 166.

#### Hand protection:

In case of repeated or prolonged contact wear gloves. The gloves should be replaced immediately in case of damage or signs of wear. It is recommended to use preventative skin protection (skin cream). The protection glove should be tested for its specific suitability (e.g. mechanical strength, product compatibility, anti-static properties).

#### Other skin protection

#### Materials for protective clothing:

Neoprene or nitrile rubber gloves. PVC gloves. Chemical resistant gloves (according to European standard NF EN 374 or equivalent)

### Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

#### 8.2.2.3. Respiratory protection

#### **Respiratory protection:**

Respiratory protective equipment is not normally required where there is adequate natural or local exhaust ventilation to control exposure. Where excessive vapour, mist, or dust may result, use approved respiratory protection equipment. Respiratory protective equipment must be checked to ensure it fits correctly each time it is worn. Provided an air-filtering/air-purifying respirator is suitable, a filter for particulates can be used for mist or fume. Use filter type P or comparable standard. A combination filter for particles and organic gases and vapours (boiling point >65°C) may be required if vapour or abnormal odour is also present due to high product temperature. Use filter type AP or comparable standard.

#### 8.2.2.4. Thermal hazards

No additional information available

#### 8.2.3. Environmental exposure controls

#### Environmental exposure controls:

See Heading 12. See Heading 6.

#### Consumer exposure controls:

Provide good ventilation in process area to prevent formation of vapour. Neoprene or nitrile rubber gloves. PVC gloves.

#### Other information:

Do not put the product-soaked rags into the pockets of working clothes. Do not use cloths stained with the product to dry hands. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Do not eat, drink or smoke during use. Wash contaminated clothing before reuse.

#### **SECTION 9: Physical and chemical properties**

#### 9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Appearance	: Liquid.
Colour	: Blue.
Odour	: characteristic. lemon odour.
Odour threshold	: No data available
pH	: 7
Relative evaporation rate (butylacetate=1)	: < 0,1
Melting point	: ≤ -45 °C
Freezing point	: No data available
Boiling point	: > 78 °C
Flash point	: 23 °C
Auto-ignition temperature	: > 200 °C
Decomposition temperature	: No data available
Flammability (solid, gas)	: No data available
Vapour Pressure 20°C	: < 23 hPa
Relative vapour density at 20°C	: > 1 (air = 1)
Relative density	: No data available
Density	: 0,905 – 0,92 kg/l
Solubility	: Soluble in water.
Log Pow	: < 0,1
Viscosity, kinematic	: 1 mm²/s
Viscosity, dynamic	: No data available
Explosive properties	: No data available
Oxidising properties	: No data available
Explosive limits	: 3,5 – 15 vol %

#### 9.2. Other information

VOC content

: 50-60 %

#### **SECTION 10: Stability and reactivity**

#### 10.1. Reactivity

Stable under normal conditions of use.

### Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

10.2. Chemical stability
Stable under normal conditions.
10.3. Possibility of hazardous reactions
Refer to section 10.1 on Reactivity.
10.4. Conditions to avoid
Keep away from naked flames/heat.
10.5. Incompatible materials
Strong oxidizing agents. Strong acids.

10.6. Hazardous decomposition products

CO, CO2.

SECTION 11: Toxicological information	
11.1 Information on toxicological effects	
Acute toxicity (dermal)	Not classified Not classified Not classified
ethanol; ethyl alcohol (64-17-5)	
LD50 oral rat	7060 – 10470 mg/kg
LD50 dermal rabbit	> 15800 mg/kg
LC50 Inhalation - Rat	51 mg/l/4h
LC50 Inhalation - Rat (Dust/Mist)	124,7 mg/l/4h
ethane-1,2-diol (107-21-1)	
LD50 oral rat	4000 mg/kg
LD50 dermal	> 3500 mg/kg mouse
LC50 Inhalation - Rat	> 2,5 mg/l (6h)
butanone; ethyl methyl ketone (78-93-3)	
LD50 oral rat	2737 mg/kg
LD50 dermal rabbit	6480 mg/kg
LC50 Inhalation - Rat (Dust/Mist)	34 mg/l/4h
Skin corrosion/irritation :	Not classified
Serious eye damage/irritation :	pH: 7 Causes serious eye irritation. pH: 7
······································	Not classified
g	Not classified
- 5 ,	Not classified
, ,	Not classified
	Not classified
butanone; ethyl methyl ketone (78-93-3)	
STOT-single exposure	May cause drowsiness or dizziness.
STOT-repeated exposure :	Not classified

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

ethane-1,2-diol (107-21-1)		
STOT-repeated exposure May cause damage to organs through prolonged or repeated exposure.		
butanone; ethyl methyl ketone (78-93-3)		
NOAEC (inhalation, rat, gas, 90 days)	2500 ppmv/6h/day	
	Not classified May be fatal if swallowed and enters airways	
Eurol Screenwash Concentrate		
Viscosity, kinematic	1 mm²/s	

SECTION 12: Ecological information			
12.1. Toxicity			
Hazardous to the aquatic environment, short–term : (acute)	Ecotoxicological data have not been determined specifically for this product. Information given is based on a knowledge of the components and the ecotoxicology of similar products. Not classified		
ethanol; ethyl alcohol (64-17-5)			
LC50 fish 1	12 – 16 ml/l (Oncorhynchus mykiss [static])		
LC50 fish 2	> 100 mg/l (Pimephales promelas [static])		
EC50 Daphnia 1	9268 – 14221 mg/l (Daphnia magna)		
EC50 Daphnia 2	10800 mg/l (24 h; Daphnia magna)		
Threshold limit algae 1	1450 mg/l (192 h; Microcystis aeruginosa)		
Threshold limit algae 2	5000 mg/l (168 h; Scenedesmus quadricauda)		
ethane-1,2-diol (107-21-1)			
LC50 fish 1	72860 mg/l Pimephales promelas		
EC50 Daphnia 1	46300 mg/l		
butanone; ethyl methyl ketone (78-93-3)			
LC50 fish 1	3130 – 3320 mg/l (96 h ; Pimephales promelas [flow-trough])		
EC50 Daphnia 1	> 520 mg/l (48 h ; Daphnia magna)		
EC50 Daphnia 2	5091 mg/l (48 h ; Daphnia magna)		
EC50 72h - Algae [1]	1972 mg/l Pseudokirchneriella subcapitata		

### 12.2. Persistence and degradability

Eurol Screenwash Concentrate		
Persistence and degradability	Readily biodegradable in water. The surfactant(s) contained in this preparation complies(comply) with the biodegradability criteria as laid down in Regulation (EC) No. 648/2004 on detergents. Data to support this assertion are held at the disposal of the competent authorities of the Member States and will be made available to them, at their direct request or at the request of a detergent manufacturer.	
ethanol; ethyl alcohol (64-17-5)		
Persistence and degradability	Readily biodegradable in water. Biodegradable in the soil. No (test)data on mobility of the substance available.	

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

ethane-1,2-diol (107-21-1)				
Persistence and degradability	Readily biodegradable in water. easily degradable in the soil.			
Biochemical oxygen demand (BOD)	0,47 g O₂/g substance			
Chemical oxygen demand (COD)	1,24 g O₂/g substance			
ThOD	1,29 g O <sub>2</sub> /g substance			
BOD (% of ThOD)	0,36			
butanone; ethyl methyl ketone (78-93-3)				
Biodegradation	98 % 28 d			
12.3. Bioaccumulative potential				
Eurol Screenwash Concentrate				
Log Pow	< 0,1			
Bioaccumulative potential	This product is not expected to bioaccumulate through food chains in the environment.			
ethanol; ethyl alcohol (64-17-5)				
Log Pow	-0,31			
ethane-1,2-diol (107-21-1)				
Log Pow	-1,36			
Bioaccumulative potential	No bioaccumulation.			
butanone; ethyl methyl ketone (78-93-3)				
Log Pow	≤ 4			
12.4. Mobility in soil				
Eurol Screenwash Concentrate				
Ecology - soil	Spillages may penetrate the soil causing ground water contamination.			
ethanol; ethyl alcohol (64-17-5)				
Ecology - soil	Spillages may penetrate the soil causing ground water contamination. Completely miscible with water.			
ethane-1,2-diol (107-21-1)				
Surface tension	0,048 N/m (20 °C)			
12.5. Results of PBT and vPvB assessment				
No additional information available				
12.6. Other adverse effects				

No additional information available

SECTION 13: Disposal considerations	
13.1. Waste treatment methods	
Regional legislation (waste) Waste disposal recommendations	<ul> <li>Disposal must be done according to official regulations.</li> <li>Dispose in a safe manner in accordance with local/national regulations. Do not discharge into drains or the environment.</li> </ul>
Additional information	: Hazardous waste.
Ecology - waste materials	: When not empty dispose of this container at hazardous or special waste collection point.

### Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

European List of Waste (LoW) code

: 07 06 04\* - other organic solvents, washing liquids and mother liquors

n accordance with ADR / IME	)G / IATA / ADN / RID			
ADR	IMDG	ΙΑΤΑ	ADN	RID
14.1. UN number			'	
UN 1170	UN 1170	UN 1170	UN 1170	UN 1170
14.2. UN proper shippin	g name		1	
ETHANOL SOLUTION (ETHYL ALCOHOL SOLUTION)	ETHANOL SOLUTION (ETHYL ALCOHOL SOLUTION)	_COHOL (ETHYL ALCOHOL		ETHANOL SOLUTION (ETHYL ALCOHOL SOLUTION)
Transport document descr	iption		1	
UN 1170 ETHANOL SOLUTION (ETHYL ALCOHOL SOLUTION), 3, III, (D/E)	UN 1170 ETHANOL SOLUTION (ETHYL ALCOHOL SOLUTION), 3, III	UN 1170 Ethanol solution, 3, III	UN 1170 ETHANOL SOLUTION (ETHYL ALCOHOL SOLUTION), 3, III	UN 1170 ETHANOL SOLUTION (ETHYL ALCOHOL SOLUTION), 3 III
14.3. Transport hazard o	class(es)		-	
3	3	3	3	3
3				
14.4. Packing group			1	
III	III	III	III	Ш
14.5. Environmental haz	ards		1	
Dangerous for the environment: No	Dangerous for the environment: No Marine pollutant: No	Dangerous for the environment: No	Dangerous for the environment: No	Dangerous for the environment: No

### 14.6. Special precautions for user

Overland transport		
Classification code (UN)	:	F1
Special provisions (ADR)	:	144, 601
Limited quantities (ADR 2011)	:	51
Excepted quantities (ADR)	:	E1
Packing instructions (ADR)	:	P001, IBC03, LP01, R001
Mixed packing provisions (ADR)	:	MP19
Portable tank and bulk container instructions (ADR)	:	T2
Portable tank and bulk container special provisions	:	TP1
(ADR)		
Tank code (ADR)	:	LGBF
Vehicle for tank carriage	:	FL
Transport category (ADR)	:	3
Special provisions for carriage - Packages (ADR)	:	V12
Special provisions for carriage - Operation (ADR)	:	S2
Hazard identification number (Kemler No.)	:	30
Orange plates	:	30
		1170

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

Tunnel restriction code (ADR)	: D/E
EAC code	: •2YE
Transport by sea	
Special provisions (IMDG)	: 144, 223
Limited quantities (IMDG)	: 5L
Excepted quantities (IMDG)	: E1
Packing instructions (IMDG)	: P001, LP01
IBC packing instructions (IMDG)	: IBC03
Tank instructions (IMDG)	: T2
Tank special provisions (IMDG)	: T2 : TP1
EmS-No. (Fire)	: F-E : S-D
EmS-No. (Spillage)	
Stowage category (IMDG)	: A
Flash point (IMDG)	: 23°C
Properties and observations (IMDG)	: Colourless, volatile liquids.Pure ETHANOL: flashpoint 13°C c.c. Explosive limits: 3.3% to
	19% Miscible with water.
Air transport	
PCA Excepted quantities (IATA)	: E1
PCA Limited quantities (IATA)	: Y344
PCA limited quantity max net quantity (IATA)	: 10L
PCA packing instructions (IATA)	: 355
PCA max net quantity (IATA)	: 60L
CAO packing instructions (IATA)	: 366
CAO max net quantity (IATA)	: 220L
Special provisions (IATA)	: A3, A58, A180
ERG code (IATA)	: 3L
Inland waterway transport	
Classification code (ADN)	: F1
Special provisions (ADN)	: 144, 601
Limited quantities (ADN)	: 5L
Excepted quantities (ADN)	: E1
Carriage permitted (ADN)	: Т
Equipment required (ADN)	: PP, EX, A
Ventilation (ADN)	: VE01
Number of blue cones/lights (ADN)	: 0
Rail transport	
Classification code (RID)	: F1
Special provisions (RID)	: 144, 601
Excepted quantities (RID)	: E1
Packing instructions (RID)	: P001, IBC03, LP01, R001
Mixed packing provisions (RID)	: MP19
Portable tank and bulk container instructions (RID)	: T2
Portable tank and bulk container special provisions	: TP1
(RID)	
Tank codes for RID tanks (RID)	: LGBF
Transport category (RID)	: 3
Special provisions for carriage – Packages (RID)	: W12
Colis express (express parcels) (RID)	: CE4
Hazard identification number (RID)	: 30

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable

### Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

### SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### 15.1.1. EU-Regulations

EU restriction list (REACH Annex XVII)		
Reference code	Applicable on	
3(a)	Eurol Screenwash Concentrate ; ethanol; ethyl alcohol ; butanone; ethyl methyl ketone	
3(b)	Eurol Screenwash Concentrate ; ethanol; ethyl alcohol ; ethane-1,2-diol ; butanone; ethyl methyl ketone	
40.	ethanol; ethyl alcohol ; butanone; ethyl methyl ketone	

Contains no substance(s) listed on the REACH Candidate List

Contains no substance(s) listed on REACH Annex XIV (Authorisation List)

Contains no substance(s) listed on the PIC list (Regulation EU 649/2012 concerning the export and import of hazardous chemicals)

Contains no substance(s) listed on the POP list (Regulation EU 2019/1021 on persistent organic pollutants)

Contains no substance(s) listed on the Ozone Depletion list (Regulation EU 1005/2009 on substances that deplete the ozone layer)

Contains no substance(s) listed on the Explosives Precursors list (Regulation EU 2019/1148 on the marketing and use of explosives precursors) VOC content : 50 - 60 %

Contains substance(s) listed on the Drug Precursors list (Regulation EC 273/2004 on the manufacture and the placing on market of certain substances used in the illicit manufacture of narcotic drugs and psychotropic substances)

Name	CN designation	CAS-No.	CN code	Category	Threshold	Annex
Methylethylketone	Butanone	78-93-3	2914 12 00	Category 3		Annex I

#### 15.1.2. National regulations

No additional information available

#### 15.2. Chemical safety assessment

No additional information available

#### SECTION 16: Other information

Full text of H- and EUH-statements:			
Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4		
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2		
Flam. Liq. 2	Flammable liquids, Category 2		
H225	Highly flammable liquid and vapour.		
H226	Flammable liquid and vapour.		
H302	Harmful if swallowed.		
H319	Causes serious eye irritation.		
H336	May cause drowsiness or dizziness.		
H373	May cause damage to organs through prolonged or repeated exposure.		
STOT RE 2	Specific target organ toxicity – Repeated exposure, Category 2		
STOT SE 3	Specific target organ toxicity – Single exposure, Category 3, Narcosis		

Safety Data Sheet (SDS), EU

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.