



Quality is in our nature

Passenger car engine oils - Fully Synthetic

Eurol Fluence DXS 5W-30

Fully synthetic long-life motor oil based on mid SAPS technology

Description

Eurol Fluence DXS 5W-30 is a fully synthetic motor oil for gasoline and diesel engines in passenger cars and light duty commercial vehicles. This oil can be used in cars equipped with catalytic converters, turbo charged engines, soot filters and direct injection systems.

Eurol Fluence DXS 5W-30 not only offers an extremely good wear protection but also protects against rust and oxidation, while special additives keep the engine clean from dirt, sludge and deposits during the sometimes extremely long drain intervals.

Eurol Fluence DXS 5W-30, manufactured with Eurol's OPT additives, offers an extremely high protection over prolonged drain intervals. Especially recommended for Euro-4 cars of Opel, Mercedes Benz with soot filters to prevent filter blocking.

Eurol Fluence DXS 5W-30 fulfills the requirements of GM Dexos 2 and can also be used where GM-LL-A-025 en -B-025 are prescribed.

Because of this, Eurol Fluence DXS 5W-30 has low sulphated ash contents and also low levels of phosphor and sulphur (so called "mid SAPS" technology).

Eurol Fluence DXS 5W-30 is also suitable for all Volkswagen Seat, Audi and Skoda cars with normal drain intervals. Furthermore, this oil is an excellent choice for most Mercedes passenger cars and light duty commercial vehicles with or without a soot filter.

Specifications

<u>Approved</u>	<u>Recommended for use</u>
GM dexos 2	VW 505.00
MB-Approval 229.52	GM-LL-A-025
MB-Approval 229.51	GM-LL-B-025
<u>Performance level</u>	Fiat 9.55535-S3
API SN/CF	
ACEA C3	
VW 502.00	
VW 505.01	
MB 229.31	
BMW Longlife-04	

Physical properties

Colour	Brown	
Density at 20°C	0.85 kg/l	ASTM D 1298
Viscosity, kinematic at 40°C	66.7 cSt	ASTM D 445
Viscosity, kinematic at 100°C	11.6 cSt	ASTM D 445
Viscosity Index	170	ASTM D 2270
Viscosity, dynamic (CCS) at -30 °C	5590 cP	ASTM D 2602
MRV	22000 cP	ASTM D 4684
HTHS	3.5 cP	CEC CL 23
Base number	7.4 mg KOH/g	ASTM D 2896
Sulphated ash	0.78 wt%	ASTM D 874
Flash point	192 °C	ASTM D 93
Pour point	-39 °C	ASTM D 97

E100076

Version 3.0, 21-08-2019

This sheet contains recommendations or suggestions on properties and possible applications of Eurol products. Because of continuous product research and development, the information in this document can be changed at all times, without foregoing notice. The analytical information in this document consists of typical incorrectness of the text. The reader is advised to make the final product choice in dialogue with the supplier.

Eurol B.V. Energiestraat 12, 7442 DA Nijverdal, Netherlands, tel. +31 88 250 22 00, fax +31 548 61 01 95, info@eurol.com, www.eurol.com