



Quality is in our nature

Automatic transmission fluids - Mineral

Eurol ATF III F

Mineral automatic transmission fluid Dexron III F

Description

Eurol ATF III F is a mineral based automatic transmission fluid, especially developed for new (after 1995) and older (automatic) transmissions, build by GM, Ford and many other manufactures. It is also suitable for power steering systems, some hydraulic systems and for rotary air compressors where an excellent low temperature fluidity is required.

Eurol ATF III F has a very high viscosity index and offers resistance against corrosion and foam building. The product also has good anti oxidation and anti wear properties.

Eurol ATF III F has an extremely low pour point which allows easy gear shifting at cold starts. Seals are not affected by this ATF

Specifications

Approved Volvo 97341

ZF TE-ML 04D/14A

ZF registration no.000387

Performance level

Allison C-4

Dexron III F

Ford Mercon

Caterpillar TO-2

Recommended for use

MAN 339 Type V2

MAN 339 Z-2

Physical properties

Colour	Red	
Density at 20°C	0.859 kg/l	ASTM D 1298
Viscosity, kinematic at 40°C	37.3 cSt	ASTM D 445
Viscosity, kinematic at 100°C	7.4 cSt	ASTM D 445
Viscosity Index	169	ASTM D 2270
Flash point	196 °C	ASTM D 93
Pour point	-48 °C	ASTM D 97

E113659

Version 1.0, 04-03-2016

This sheet contains recommendations or suggestions on properties and possible applications of Eurol products. Because of continuous product research and development, the information in this document can be changed at all times, without foregoing notice. The analytical information in this document consists of typical incorrectness of the text. The reader is advised to make the final product choice in dialogue with the supplier.

Eurol B.V. Energiestraat 12, 7442 DA Nijverdal, Netherlands, tel. +31 88 250 22 00, fax +31 548 61 01 95, info@eurol.com, www.eurol.com