



Quality is in our nature

Additives - Fuel

Eurol Motorcycle Injection Cleaner

Fuel additive for cleaning motorcycle injectors

Description

Eurol Motorcycle Injection Clean is formulated to clean contaminated petrol injection systems, to restore injector efficiency and to improve fuel atomization. Removes carbon deposits and deposits from fuel lines, fuel distributors, injection and inlet valves.

Eurol Motorcycle Injection Clean is recommended for motorbikes with rough idling, stumbling due to dirty injectors (clogged injector nozzles) that are restricted due to fuel deposits or if the engine is having a hard time with tough starts or it may be running roughly.

Eurol Motorcycle Injection Clean can be used in vehicles equipped with a catalytic converter.

The 100ml bottle of Eurol Motorcycle Injection Clean is recommended for use in 15L to 25L of fuel and let the cleaner run through the fuel system.

Add the Eurol Motorcycle Injection Clean to the fuel tank before refueling. For best results use about once every

2.500 km because deposits form with every tank of fuel. Also change the air and fuel filters for regular maintenance, especially with in-city driving conditions.

After using this product, you should notice better performance from the engine when accelerating and a quieter engine when running stationary. An injection cleaner will not repair actual mechanical failures (ignition, timing, etc).

Users should consult the Material Safety Data Sheet of Eurol Motorcycle Injection Clean for information about storage and shelf life. Please ask Eurol Research & Development if any further information is required.

Physical properties

Colour	Colourless	
Density at 20°C	0.807 kg/l	ASTM D 1298
Viscosity, kinematic at 40°C	2.8 cSt	ASTM D 445
Flash point	62 °C	ASTM D 93

E802811

Version 1.0, 25-03-2016

This sheet contains recommendations or suggestions on properties and possible applications of Eurol products. Because of continuous product research and development, the information in this document can be changed at all times, without foregoing notice. The analytical information in this document consists of typical incorrectness of the text. The reader is advised to make the final product choice in dialogue with the supplier.

Eurol B.V. Energiestraat 12, 7442 DA Nijverdal, Netherlands, tel. +31 88 250 22 00, fax +31 548 61 01 95, info@eurol.com, www.eurol.com